










IP20 DIMMABLE - LED BAR

	Item No. (Code)	Power (W)	Voltage (V/mA)	LEDs	Lamp luminous lux (Lm/m)	Beam Angle (°)	Color temperature (K)	Cut Length (mm)	Remarks
	VTL-MSS2-32-30K-11.2W VTL-MSS2-32-40K-11.2W	11.2	500mA	32/pcs		120	3000 4000	150	L596 x W6.8 x H1mm
	VTL-MSS2-30-27K-14.4W VTL-MSS2-30-30K-14.4W VTL-MSS2-30-40K-14.4W	14.4	DC12V/ 1.2mA	30/pcs	115.3	120	2700 3000 4000	-	L596 x W6.8 x H1mm
	VTL-2835-600X39F-112-WH-30K-175 VTL-2835-600X39F-112-WH-40K-150 VTL-2835-600X39F-112-WH-40K-195	19	42V/ 500mA	112/ pcs	175 150 195	120	3000 4000	-	L600 x W39mm
	VTL-5630-560X20E-4X12-WH-12V	15.4	DC12V/ 120mA	48/pcs	2200/pcs	120	3000 4000	46.7 (4 LEDs)	L560 x W20mm
	VTL-5630-720X15E-4X16-WH-12V	34.5	DC12V/ 180mA	64/pcs	2200/pcs	120	3000 4000	45 (4 LEDs)	L720 x W15mm

IP20 (SIDE LED) DIMMABLE | DC12V / DC24V

	VTL-3014-1230-27I-8W-SIDE	8	DC12V	96	-	-	2700	50	3LEDs per 50mm (5M per reel)
	VTL-3014-1248-27I-11.5W-SIDE	11.5	DC12V	96	-	-	2700	33	3LEDs per 33mm (5M per reel)
	VTL-3014-2430-27I-8W-SIDE	8	DC24V	60	-	-	2700	100	6LEDs per 100mm (5M per reel)
	VTL-3014-2430-50I-8W-SIDE	8	DC24V	60	-	-	5000	100	6LEDs per 100mm (5M per reel)
	VTL-3014-2430-50I-12W-SIDE	12	DC24V	60	-	-	5000	100	6LEDs per 100mm (5M per reel)




IP20 DIMMABLE | DC12V

	VTL-2835-1230-27I-CRI80-4W	4	DC12V	60	116.4	120	2700	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-22I-CRI80-5W	5	DC12V	60	-	120	2200	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-27I-CRI80-6.5W VTL-2835-1230-30I-CRI80-6.5W	6.5	DC12V	60	109.6	120	2700 3000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-24I-CRI80-8W	8	DC12V	60	98.7	120	2400	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-30I-CRI80-12W	12	DC12V	60	111.5	120	3000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-30I-S-SHAPE-8W VTL-2835-1230-40I-S-SHAPE-8W	8	DC12V	60	-	120	3000 4000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1260-24I-CRI80-14W VTL-2835-1260-30I-CRI80-14W	14	DC12V	120	102.9	120	2400 3000	25	3LEDs per 50mm (5M per reel)



IP20 DIMMABLE | DC24V

	Item No. (Code)	Power (W)	Voltage (V)/(mA)	LEDs	Lamp luminous lux (Lm/m)	Beam Angle (°)	Color temperature (K)	Cut Length (mm)	Remarks	
	VTL-2835-2430-27I-CRI80-4W VTL-2835-2430-30I-CRI80-4W	4	DC24V	60	100	120	2700 3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-27I-CRI80-6.5W VTL-2835-2430-30I-CRI80-6.5W	6.5	DC24V	60	100	120	2700 3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-30I-CRI80-8W VTL-2835-2430-40I-CRI80-8W	8	DC24V	60	100	120	3000 4000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2460-27I-CRI80-8W	8	DC24V	120	-	120	2700	50	6LEDs per 50mm (5M per reel)	
	VTL-2835-2430-27I-CRI80-10W VTL-2835-2430-30I-CRI80-10W	10	DC24V	60	60	120	2700 3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-27I-CRI80-12W	12	DC24V	60	126	120	2700	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-27I-CRI80-14W VTL-2835-2430-30I-CRI80-14W VTL-2835-2430-40I-CRI80-14W	14	DC24V	60	-	120	2700 3000 4000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2460-27I-CRI80-14W VTL-2835-2460-30I-CRI80-14W VTL-2835-2460-40I-CRI80-14W VTL-2835-2460-50I-CRI80-14W	14	DC24V	120	-	120	2700 3000 4000 5000	50	6LEDs per 50mm (5M per reel)	
		VTL-2835-2449-27I-CRI80-19W VTL-2835-2449-24I-CRI80-19W VTL-2835-2449-30I-CRI80-19W VTL-2835-2449-40I-CRI80-19W VTL-2835-2498-50I-CRI80-19W	19	DC24V	98	87.95	120	2400 2700 3000 4000 5000	72	6LEDs per 72mm (5M per reel)
		VTL-2835-2448-27I-CRI90-19W VTL-2835-2448-60I-CRI90-17W	19 17	DC24V	96	-	120	2700 6000	83	8LEDs per 72mm (5M per reel)
			VTL-5050-2430-RGBI-14W	14	DC24V	60	-	120	RGB	100
			VTL-5050-2430-RGBW-CRI80-14W	14	DC24V	60	-	120	RGBW	100
	VTL-2835-2430-BLUEI-8W	8	DC24V	60	-	120	BLUE	100	6LEDs per 100mm (5M per reel)	




IP20 COLOR SELECTABLE LED STRIP (CCT) - CRI>90 | DC24V

	VCOL-2835-2470-27K-60I (Color Selectable)	19.2	DC24V	140			CCT	100	14LEDs per 100mm (5M per reel)
	VCOL-2216-24120-27K-60I (Color Selectable)	19.2	DC24V	240			CCT	50	12LEDs per 50mm (5M per reel)
	VCOL-2216-24120-27K-60I (Color Switchable by wall switch)	21.3	DC24V	168			CCT	83	14LEDs per 83mm (5M per reel)

IP65/1P67* DIMMABLE | DC12V

	VTL-2835-1230-270-CRI80-4W VTL-2835-1230-300-CRI80-4W VTL-2835-1230-300-CRI80-4W IP67*	4	DC12V	60	115.9	120	2700 3000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-270-CRI80-6.5W VTL-2835-1230-300-CRI80-6.5W	6.5	DC12V	60	104.1	120	2700 3000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-240-CRI80-8W	8	DC12V	60	90.83	120	2400	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1230-300-CRI80-14W	14	DC12V	60	112.6	120	3000	50	3LEDs per 50mm (5M per reel)
	VTL-2835-1260-240-CRI80-6.5W	6.5	DC12	120		120	2400	25	3LEDs per 25mm (5M per reel)
	VTL-2835-1260-240-CRI80-14W	14	DC12V	120	103	120	2400	25	3LEDs per 25mm (5M per reel)

IP65 DIMMABLE | DC24V

	Item No. (Code)	Power (W)	Voltage (V)/(mA)	LEDs	Lamp luminous lux (Lm/m)	Beam Angle (°)	Color temperature (K)	Cut Length (mm)	Remarks	
	VTL-2835-2430-300-CRI80-5W	5	DC24V	60	131.8	120	3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-270-CRI80-6W	6	DC24V	60	100	120	2700	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-400-CRI80-8W	8	DC24V	60		120	4000	80	6LEDs per 80mm (5M per reel)	
	VTL-2835-2430-300-CRI80-10W	10	DC24V	60		120	3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2430-300-CRI80-14W	14	DC24V	60	93.24	120	3000	100	6LEDs per 100mm (5M per reel)	
	VTL-2835-2460-270-CRI80-14W VTL-2835-2460-300-CRI80-14W VTL-2835-2460-300-CRI80-14W IP67* VTL-2835-2460-400-CRI80-14W	14	DC24V	120	-	120	2700 3000	50	6LEDs per 50mm (5M per reel)	
		VTL-2835-2449-240-19W VTL-2835-2449-300-19W VTL-2835-2449-400-19W VTL-2835-2449-500-19W	19	DC24V	98	-	120	2400 3000 4000 5000	71.5	7LEDs per 71.5mm (5M per reel)