



PROFESSIONAL DISPLAY/MUSEUM LIGHTING

VTS-SA-501H (Micro Spots & Track)



LED Power 3W
CoB
350mA, 12V
Beam Angle: 8°/12°/24°/36°
3000K/4000K
*93 lm for standard application
INPUT: AC 220-240V

Colours: White Black




Accessories for anti-dazzle

Features:


- Won 2012 iF Design Award (original series)
- Won 2012 Reddot Design Award: Product Design (original series)
- Won 2016 Taiwan Excellence Silver Award & 2012 Taiwan Excellence Award (original series)
- Patented circuit bridging structure: modularized play
- Smart circuit track design: bidirectional electricity input
- An innovate finger - click lamp installation

U-Shape MicroTrack

Output: DC 12V
Max Power: 6A
Length: 300 mm; 600 mm; 900 mm; 1000 mm
Color: BK




Light Distribution




H(m)	D(m)	E(lx)
1.0	0.1	1390
2.0	0.3	348
3.0	0.4	154

350mA : 1390 cd
700mA : 2480 cd




H(m)	D(m)	E(lx)
1.0	0.2	730
2.0	0.4	183
3.0	0.6	81

350mA : 730 cd
700mA : 1270 cd



H(m)	D(m)	E(lx)
1.0	0.4	310
2.0	0.9	78
3.0	1.3	34

350mA : 310 cd
700mA : 540 cd



H(m)	D(m)	E(lx)
1.0	0.6	210
2.0	1.3	53
3.0	1.9	23

350mA : 210 cd
700mA : 365 cd

Ordering Code: VTS-SA-501H - YYD - ZZZ - CC

Example: VTS-SA-501H-36D-930-BK

YY = Beam angle in degrees.

CC = Fitting Color: WH: White, BK: Black

ZZZ = the code for color rendering and color temperature, eg. 830 = CRI >80 and CCT - 3000K; 940 = CRI >90 and CCT - 4000K *CRI: > 90 available