

VISION+LITE LED Spotlight System

IP65 MICRO SPOT LIGHT | Adjustable

VLD-ALUM SLICE



LED POWER : 1 x 1.2W (350mA)
 LED : PHILIPS LUMILED REBEL S (color LED on request)
 Beam Angle : 12°/24°/36°
 CCT(K) : 2700K, 3000K
 Driver : Remote driver, constant current 350mA
 Material : Turned aluminium, stainless steel screws, neoprene cable-2M
 Color : Black
 Optional wattage : 2W at 500mA

- Option of 1 driver to 1 lamp or 1 driver to multiple lamps in series circuit.
- Multi-lamp drivers available for: 3, 5, 10 and 15 lamps
- Choice of drivers dimmable by trailing edge/leading edge or 0-10V DC or DALI



Sri Mariamman Temple, Singapore

Ordering Code: VLD-ALUM SLICE - YYD - ZZZ

Example: VLD-ALUM SLICE-12D-830-BK

V = 6606, 6607

YY = Beam angle in degree: 12, 24, 36deg

CC is Fixture Color, BK = Black

ZZZ = the code for color rendering and color temperature, eg. **827** = CRI >80 and CCT - 2700K; **830** = CRI >80 and CCT - 3000K; **840** = CRI >80 and CCT - 4000K